

# 2009 NHRA E.T. Quick Reference Chart

1/4 Mile E.T.	6.00 TO 7.49	7.50 TO 9.99	10.00 TO 10.99	11.00 TO 11.49	11.50 TO 13.99	14.00 & SLOWER
1/8 Mile E.T.	3.66 TO 4.49	4.50 TO 6.39	6.40 TO 6.99	7.00 TO 7.35	7.36 TO 8.59	8.60 & SLOWER
Aftermarket Rear Axles	Y	Y	Y	2:11	2:11	2:11
Arm Restraints (Open Cars)	Y	Y	Y	Y	10:3 11.99	10:3
Auto Trans Flexplate (SFI 29-1)	Y	Y	2:14	2:14	2:14	2:14
Auto Trans Reverse Lockout	Y	Y	Y	Y	Y	Y
Bellhousing (SFI 6-1/6-2)	Y	Y	Y	Y	2:10	2:10
Driver Restraint System (SFI 16-1)	Y	Y	Y 10:5	Y 10:5	C 10:5	10:5 10:11
Driveshaft Loop	Y	Y	Y	Y	2:4	2:4
Electric 16.00 & Quicker	Y	Y	Y	Y	Y	2:4
Flexplate Shield (SFI 30-1)	Y	Y	2:14	2:14	2:14	2:14
Flywheel/Clutch (SFI 1-1/1-2)	Y	Y	Y	Y	2:5	2:5
Harmonic Balancer (SFI 18-1)	Y	Y	Y	Permitted	Permitted	Permitted
Helmet (Snell 2000 or SFI 41-1 A min.)	Y	Y	Y	Y	Y	10:7
Liquid Overflow	Y	Y	Y	Y	Y	Y
Master Electrical Cutoff	Y	Y	8:4 135 mph	8:4	8:4	8:4
Neck Collar	Y	Y	10:8	10:8	10:8	10:8
NHRA Competition License	Y	Y	10:4	10:4	10:4	10:4
NHRA Chassis Sticker	Y	Y	4:4	4:4	4:4	4:4
Padding Roll Bar/Cage	Y SFI	Y	Y	Y	10:6 135 mph	10:6 135 mph
Parachute	Y	Y	4:8 150 mph	4:8	4:8	4:8
Pressurized Bottles DOT (1800)	Y	Y	Y	Y	Y	Y
Protective Clothing	Y	Y	Y	Y	10:10	10:10
Roll Bar			Y	Y	C/13.49	4:10
Roll Cage	Y	Y	Y 135 mph	4:11	4:11	4:11
SFI Chassis Specification	Y	4:4 180 mph	4:4	4:4	4:4	4:4
Supercharger Restraints	Y	1:11	1:11	1:11	1:11	1:11
Tail Light	Y	Y	Y	Y	Y	Y
Transmission Shield (SFI 4-1)	Y	Y	Y	2:14	2:14	2:14
Window Net (Full-Bodied Cars)	Y	Y	6:3 10:3	6:3 10:3	6:3 10:3	6:3 10:3

Y = Required    C = Convertibles

Number Refers to General Regulations

In no way is this Quick Reference Chart intended to supersede or replace the current NHRA Rulebook